


**Features:**

- AC Input Range : 90~277Vac
- AC Inrush Current : <10A, 240Vac Cold start
- Power Factor : >0.95, 120V ; >0.90, 240V
- 2 Channel Output
- Tunable White & Brightness Control
- Protection: SCP, OVP, OTP
- Operating Ambient Temp : -20°C ~ +55 °C
- Safety: MEET ENEC, CCC UL, PSE, CNS
- EMC: MEET CE, FCC, VCCI
- Lifetime : 35,000 hrs , Ta=40 °C

**SPECIFICATION**

Model		BLE-D007
Output	Output Power	7~15 W
	Output Voltage	30~46V
	Number of Channels	2 channels
	Output Current	150mA~320mA
	Output Current Tolerance	± 5%
	Output Current Ripple	± 5%
Input	Input Voltage Range	90~277VAC
	Efficiency (Typ.)	> 82%
	Power Factor (Typ.)	>0.95, 120V ; >0.90, 240V
	Inrush Current	<10A, 240Vac Cold start
Protection	OVP	Shut down o/p voltage with auto-recovery or re-power on to recovery
	SCP	Recovers automatically after fault condition is removed
	OTP	Recovers automatically after temperature goes down
Environment	Operating Temperature	-20°C ~ +55 °C
Safety & EMC	Safety*	Compliance to ENEC, CCC UL, PSE, CNS
	EMC	Compliance to CE, FCC, VCCI
Others	Dimming Type	Bluetooth control
	Dimming Range	1% to 100%
	Dimension (LxWxH)	L130x W43x H21 mm
	Lifetime	35,000 hrs, Ta= 40°C

\*Meet safety regulations standard, and ready for safety certification application according to needs.