



Features:

- AC Input Range : 100~264Vac
- AC Inrush Current : <10A, 240Vac Cold start
- Power Factor : >0.92, 240V
- 2 Channel Output
- Tunable White & Brightness Control
- Protection: SCP
- Operating Ambient Temp : -20°C ~ +45 °C
- Safety: MEET ENEC, CCC UL, PSE, CNS
- EMC: MEET CE
- Lifetime : 50,000 hrs , Ta=40 °C

SPECIFICATION

Model		BLE-D015
Output	Output Power	15W
	Output Voltage	20~40V
	Number of Channels	2 channels
	Output Current	350mA
	Output Current Tolerance	± 5%
	Output Current Ripple	± 10%
Input	Input Voltage Range	100~264Vac
	Efficiency (Typ.)	> 83.5%
	Power Factor (Typ.)	>0.92, 240V
	Inrush Current	<10A, 240Vac Cold start
Protection	OVP	Shut down o/p voltage with auto-recovery or re-power on to recovery
	SCP	Recovers automatically after fault condition is removed
	OTP	Recovers automatically after temperature goes down
Environment	Operating Temperature	-20°C ~ +45 °C
Safety & EMC	Safety*	Compliance to ENEC, CCC UL, PSE, CNS
	EMC	Compliance to CE
Others	Dimming Type	Bluetooth control
	Dimming Range	1% to 100%
	Dimension (LxWxH)	L183 x W46 x H18.2 mm
	Lifetime	50,000 hrs, Ta= 40°C

*Meet safety regulations standard, and ready for safety certification application according to needs.